

American AVK Resilient Wedge Gate Valve Class Code/ Ref. # / Breakdown

AA	-	BBB	-	CC	-	D
Series no.		Valve size		Flange config.		Stem type/Option
03 - Small Ductile		032 - 1" *		EE - PExPE		C - Cut-in
18 - Combitee		040 - 1.25" *		FF - FLxFL		F - Fitting
25 - Full Wall Grey Iron		050 - 2"		GG - GRxGR		H - High Pressure
45 - Full Wall Ductile		063 - 2" *		II - IPSxIPS		N - NRS
55 - Large Diameter Ductile		065 - 2.5"		HF - HYxFL		O - OS&Y
65 - Reduced Wall Ductile		070 - 2.5" *		HH - HYxHY		P - PIV
66 - HDPE Ends Ductile		080 - 3"		ME - MJxPE		T - Tapping
		090 - 3" *		MF - MJxFL		
		100 - 4"		MM - MJxMJ		
		150 - 6"		PF - POxFL		
		200 - 8"		PP - POxPO		
		250 - 10"		TT - NPTxNPT		
		300 - 12"				
		350 - 14"				
		400 - 16"				
		450 - 18"				
		500 - 20"				
		600 - 24"				
		800 - 30"				
		900 - 36"				






* For Series 03 only

SERIES 65 AWWA C515

REDUCED WALL DUCTILE

Size	FLxFL	HYxFL	HYxHY	MJxFL	MJxMJ	POxFL	POxPO
2"			X				
2.5"	X*		X				
3"	X	X	X	X	X		
4"	X	X	X	X	X	X	X
6"	X	X	X	X	X	X	X
8"	X	X	X	X	X	X	X
10"	X	X	X	X	X	X	X
12"	X	X	X	X	X	X	X

* Sizes below 3" not included in AWWA Standards

Type	AVK Ref. #	Size	Weight		Price US \$
			kg	lb	
Series 65/FFN REDUCED WALL DUCTILE FL X FL To AWWA C515 Flanged ends to ASME B 16.42 Class 150 NRS Ductile iron 250 PSI Size 2.5"-12"					
	65-065-FFN	2.5"	17	38	875
	65-080-FFN	3"	21	46	1,039
	65-100-FFN	4"	28	62	1,161
	65-150-FFN	6"	47	103	1,551
	65-200-FFN	8"	66	146	2,425
	65-250-FFN	10"	102	224	3,851
	65-300-FFN	12"	141	310	4,651
For 2" valves see Series 25 pg#17					
Series 65/HFN REDUCED WALL DUCTILE HY X FL To AWWA C515 HYMAX GRIP® X Flanged end to ANSI B 16.1 Class 125 NRS Ductile iron 250 PSI Size 4"-12"					
	65-100-HFN	4"	34	73	1,347
	65-150-HFN	6"	54	119	1,811
	65-200-HFN	8"	78	170	2,717
	65-250-HFN	10"	115	253	4,277
	65-300-HFN	12"	151	331	5,357
All adders are added to List Pricing Add \$60 for anode machining					
Series 65/HHN REDUCED WALL DUCTILE HY X HY To AWWA C515 HYMAX GRIP® ends Class 150 NRS Ductile iron 250 PSI Size 1.5"-12"					
	65-050-HHN	1.5"-2"	38	83	1,068
	65-065-HHN	2.5"	38	83	1,293
	65-080-HHN	3"	38	83	1,436
	65-100-HHN	4"	38	83	1,599
	65-150-HHN	6"	60	131	2,123
	65-200-HHN	8"	88	193	3,329
	65-250-HHN	10"	127	279	4,843
	65-300-HHN	12"	159	349	6,017
	All adders are added to List Pricing Add \$60 for anode machining				
Series 65/MFN REDUCED WALL DUCTILE MJ X FL To AWWA C515 Mechanical joint end X Flanged end to ANSI B 16.1 Class 125 NRS Ductile iron 250 PSI Size 3"-12"					
	less MJ accessories				
	65-080-MFN	3"	19	42	995
	65-100-MFN	4"	25	54	1,119
	65-150-MFN	6"	43	95	1,495
	65-200-MFN	8"	63	139	2,335
	65-250-MFN	10"	90	199	3,709
	65-300-MFN	12"	135	297	4,479
All adders are added to List Pricing Add \$60 for anode machining					
Series 65/MMN REDUCED WALL DUCTILE MJ X MJ To AWWA C515 To AWWA C515 Mechanical joint ends NRS Ductile iron 250 PSI Size 3"-12"					
	less MJ accessories				
	65-080-MMN	3"	19	42	1,049
	65-100-MMN	4"	24	52	1,171
	65-150-MMN	6"	42	93	1,495
	65-200-MMN	8"	59	129	2,379
	65-250-MMN	10"	89	195	3,709
65-300-MMN	12"	127	279	4,693	
For 2" valves see Series 25 pg#17 All adders are added to List Pricing Add \$60 for anode machining					

<p>Type</p> <p>Series 65/PFN REDUCED WALL DUCTILE PO X FL To AWWA C515</p> <p>Push-on joint end (TYTON) X Flanged end to ASME B 16.42 Class 150 NRS Ductile iron 250 PSI Size 4"-12"</p>	<table border="1"> <thead> <tr> <th data-bbox="579 98 878 268"> <p>AVK Ref. #</p> </th> <th data-bbox="878 98 1089 268"> <p>Size</p> </th> <th colspan="2" data-bbox="1089 98 1414 268"> <p>Weight</p> <p>kg lb</p> </th> <th data-bbox="1414 98 1541 268"> <p>Price</p> <p>US \$</p> </th> </tr> </thead> <tbody> <tr> <td>65-100-PFN</td> <td>4"</td> <td>26</td> <td>58</td> <td>1,181</td> </tr> <tr> <td>65-150-PFN</td> <td>6"</td> <td>43</td> <td>95</td> <td>1,557</td> </tr> <tr> <td>65-200-PFN</td> <td>8"</td> <td>65</td> <td>142</td> <td>2,459</td> </tr> <tr> <td>65-250-PFN</td> <td>10"</td> <td>96</td> <td>212</td> <td>3,867</td> </tr> <tr> <td>65-300-PFN</td> <td>12"</td> <td>130</td> <td>287</td> <td>4,757</td> </tr> </tbody> </table> <p>All adders are added to List Pricing Add \$60 for anode machining</p>	<p>AVK Ref. #</p>	<p>Size</p>	<p>Weight</p> <p>kg lb</p>		<p>Price</p> <p>US \$</p>	65-100-PFN	4"	26	58	1,181	65-150-PFN	6"	43	95	1,557	65-200-PFN	8"	65	142	2,459	65-250-PFN	10"	96	212	3,867	65-300-PFN	12"	130	287	4,757
<p>AVK Ref. #</p>	<p>Size</p>	<p>Weight</p> <p>kg lb</p>		<p>Price</p> <p>US \$</p>																											
65-100-PFN	4"	26	58	1,181																											
65-150-PFN	6"	43	95	1,557																											
65-200-PFN	8"	65	142	2,459																											
65-250-PFN	10"	96	212	3,867																											
65-300-PFN	12"	130	287	4,757																											
<p>Series 65/PPN REDUCED WALL DUCTILE PO X PO To AWWA C515</p> <p>Push-on joint ends (TYTON) NRS Ductile iron 250 PSI Size 4"-12"</p>	<table border="1"> <tbody> <tr> <td>65-100-PPN</td> <td>4"</td> <td>26</td> <td>56</td> <td>1,203</td> </tr> <tr> <td>65-150-PPN</td> <td>6"</td> <td>43</td> <td>95</td> <td>1,583</td> </tr> <tr> <td>65-200-PPN</td> <td>8"</td> <td>65</td> <td>142</td> <td>2,403</td> </tr> <tr> <td>65-250-PPN</td> <td>10"</td> <td>96</td> <td>212</td> <td>3,881</td> </tr> <tr> <td>65-300-PPN</td> <td>12"</td> <td>130</td> <td>287</td> <td>4,865</td> </tr> </tbody> </table> <p>All adders are added to List Pricing Add \$60 for anode machining</p>	65-100-PPN	4"	26	56	1,203	65-150-PPN	6"	43	95	1,583	65-200-PPN	8"	65	142	2,403	65-250-PPN	10"	96	212	3,881	65-300-PPN	12"	130	287	4,865					
65-100-PPN	4"	26	56	1,203																											
65-150-PPN	6"	43	95	1,583																											
65-200-PPN	8"	65	142	2,403																											
65-250-PPN	10"	96	212	3,881																											
65-300-PPN	12"	130	287	4,865																											

