







AVK Series 766, Double Eccentric Butterfly Valve Class Code/ Ref. # / Breakdown

766 - Series No.	XXXX - Size	XX - Flange Configuration	XX - Actuation	X - Opening Direction	X - Testing Pressure	X - Test Direction
	0600 - 24" 0750 - 30" 0900 - 36" 1050 - 42" 1200 - 48"	FF - FLxFL MM - MJxMJ	AG - Above Ground BG - Below Ground BS - Bare Shaft	L - Open Left R - Open Right B - Both *	L - 150 PSI H - 250 PSI	1 - Single 2 - Bi-directional

* - Only on bare stem valves

SERIES 766, DOUBLE ECCENTRIC BUTTERFLY VALVE ACRONYMS :

ANSI - American National Standards Institute
 ASME - American Society of Mechanical Engineers
 AWWA - American Water Works Association
 DI - Ductile Iron
 EPDM - Ethylene Propylene Diene Monomer
 FL - Flange
 MJ - Mechanical Joint
 WAF - Wafer
 FF - Flange x Flange
 MF - Mechanical Joint x Flange
 WW - Wafer

Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
Series766/FF/RGB-1 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Flanged end to ANSI B 16.1 Class 125 Ductile iron 150 PSI Size 24"-48"		766-0600-FF-RGB	24"	425	936	9,840
		766-0750-FF-RGB	30"	764	1684	16,900
		766-0900-FF-RGB	36"	1130	2490	20,500
		766-1050-FF-RGB	42"	1685	3715	31,750
		766-1200-FF-RGB	48"	2282	5029	40,950
		Specify above ground, or below ground installation when ordering				
Series766/FF/RGB-2 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Flanged end to ANSI B 16.1 Class 125 Ductile iron 150 PSI Size 24"-48" Bi-Directional Testing		766-0600-FF-RGB-2	24"	425	936	11,316
		766-0750-FF-RGB-2	30"	764	1684	19,435
		766-0900-FF-RGB-2	36"	1130	2490	23,575
		766-1050-FF-RGB-2	42"	1685	3715	36,513
		766-1200-FF-RGB-2	48"	2282	5029	47,093
		Specify above ground, or below ground installation when ordering				
Series766/FF/RGB-1 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Flanged end to ANSI B 16.1 Class 125 Ductile iron 250 PSI Size 24"-48"		766-0600-FF-RGB-H	24"	425	936	11,808
		766-0750-FF-RGB-H	30"	764	1684	20,280
		766-0900-FF-RGB-H	36"	1130	2490	24,600
		766-1050-FF-RGB-H	42"	1685	3715	38,100
		766-1200-FF-RGB-H	48"	2282	5029	49,140
		Specify above ground, or below ground installation when ordering				
Series766/FF/RGB-2 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Flanged end to ANSI B 16.1 Class 125 Ductile iron 250 PSI Size 24"-48" Bi-Directional Testing		766-0600-FF-RGB-H2	24"	425	936	12,989
		766-0750-FF-RGB-H2	30"	764	1684	22,308
		766-0900-FF-RGB-H2	36"	1130	2490	27,060
		766-1050-FF-RGB-H2	42"	1685	3715	41,910
		766-1200-FF-RGB-H2	48"	2282	5029	54,054
		Specify above ground, or below ground installation when ordering				
Series766/MM/RGB-1 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Mechanical Joint ends Ductile iron 150 PSI Size 24"-48"		766-0600-MM-RGB	24"	429	944	9,840
		766-0750-MM-RGB	30"	756	1667	16,900
		766-0900-MM-RGB	36"	1160	2557	20,500
		766-1050-MM-RGB	42"	1720	3790	31,750
		766-1200-MM-RGB	48"	2319	5111	40,950
		Specify above ground, or below ground installation when ordering				
Series766/MM/RGB-2 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Mechanical Joint ends Ductile iron 150 PSI Size 24"-48" Bi-Directional Testing		766-0600-MM-RGB-2	24"	429	944	11,316
		766-0750-MM-RGB-2	30"	756	1667	19,435
		766-0900-MM-RGB-2	36"	1160	2557	23,575
		766-1050-MM-RGB-2	42"	1720	3790	36,513
		766-1200-MM-RGB-2	48"	2309	5111	47,093
		Specify above ground, or below ground installation when ordering				

Type

**Series766/MM/RGB-2
DOUBLE ECCENTRIC
BUTTERFLY VALVE
To AWWA C504**


Mechanical Joint ends

Ductile iron

250 PSI

Size 24"-48"

Bi-Directional Testing



AVK Ref. #	Size	Weight - Poly kg lb	Weight - Steel kg lb	Price - Poly US \$	Price - Steel US \$
------------	------	------------------------	-------------------------	-----------------------	------------------------

766-0600-MM-RGB-H	24"		429 944		11,808
766-0750-MM-RGB-H	30"		756 1667		20,280
766-0900-MM-RGB-H	36"		1160 2557		24,600
766-1050-MM-RGB-H	42"		1720 3790		38,100
766-1200-MM-RGB-H	48"		2309 5111		49,140

Specify above ground, or below ground installation when ordering

**Series766/MM/RGB-2
DOUBLE ECCENTRIC
BUTTERFLY VALVE
To AWWA C504**


Mechanical Joint ends

Ductile iron

250 PSI

Size 24"-48"

Bi-Directional Testing



766-0600-MM-RGB-H2	24"		429 944		12,989
766-0750-MM-RGB-H2	30"		756 1667		22,308
766-0900-MM-RGB-H2	36"		1160 2557		27,060
766-1050-MM-RGB-H2	42"		1720 3790		41,910
766-1200-MM-RGB-H2	48"		2309 5111		54,054

Specify above ground, or below ground installation when ordering