

SERIES 55, AWWA C515

# LARGE DIAMETER DUCTILE

**Series 55 AWWA Availability Listing**

Size	FLxFL	MJxFL	MJxMJ
18"	X	X *	X
20"	X	X *	X
24"	X	X *	X
30"	X **	X **	X **
36"	X	X	X

\* MJxFL Adaptor Kit on FLxFL valve and MJxFL can be used as tapping valve


\*\* Integral Bypass Flanges on long lay length

AWWA C515, LARGE DIAMETER DUCTILE, RESILIENT WEDGE GATE VALVES

**Type**

**Series 55/FFN  
LARGE DIAMETER C515  
FLxFL**

Full wall ductile iron  
Flanged ends to  
ANSI B 16.1,  
Class 150 NRS  
250 PSI  
Size 18", 20", 24", 30", 36"



**AVK Ref. #**

**Size**

**Weight  
kg lb**

**Price  
US \$**

55-450-FFN	18"	599	1321	25,745
55-500-FFN	20"	639	1408	30,919
55-600-FFN	24"	856	1886	43,963
55-800-FFN	30"	2434	5366	76,700
55-900-FFN	36"	3780	8332	122,700


30" FLxFL available in lay lengths of 26" - Short, and 39" - Long. Long lay length has integral bypass flanges for mounting bypass valve assembly. Specify lay length when ordering.

All 30"-36" valves are supplied with actuation.

Use Series 55 valve discount

**Series 55/MFN  
LARGE DIAMETER C515  
MJ X FL**

Full wall ductile iron  
Mechanical joint end  
X Flanged end to  
ANSI B 16.1  
Class 150 NRS  
250 PSI  
Size 18", 20", 24", 30", 36"



less MJ accessories

55-450-MFN	18"	XXXX	XXXX	25,745
55-500-MFN	20"	XXXX	XXXX	30,919
55-600-MFN	24"	XXXX	XXXX	43,963
55-800-MFN	30"	XXXX	XXXX	76,700
55-900-MFN	36"	3812	8404	122,700

18", 20", 24", FLxFL valve with MJxFL adaptor, less MJ accessories


30", Integral bypass flanges

All 30"-36" valves are supplied with actuation.

Use Series 55 valve discount

**Series 55/MMN  
LARGE DIAMETER C515  
MJxMJ**

Full wall ductile iron  
Mechanical joint ends  
NRS  
250 PSI  
Size 18", 20", 24", 30", 36"



less MJ accessories

55-450-MMN	18"	603	1330	25,745
55-500-MMN	20"	635	1400	30,919
55-600-MMN	24"	847	1867	43,963
55-800-MMN	30"	2472	5450	76,700
55-900-MMN	36"	5151	11354	122,700

30", Integral bypass flanges


All 30"-36" valves are supplied with actuation.

Use Series 55 valve discount

**Type**

**Series 55/FFO/MO  
LARGE DIAMETER C515  
FLxFL OS&Y  
MANUAL OPERATION**

Full wall ductile iron  
Flanged ends to  
ANSI B 16.1,  
Class 150 NRS  
250 PSI  
Size 18", 20", 24"



**AVK Ref. #**

**Size**

**Weight  
kg lb**


**Price  
US \$**

55-450-FFO-MO	18"	599	1321	28,820
55-500-FFO-MO	20"	639	1408	36,180
55-600-FFO-MO	24"	856	1886	49,990

Use 14"-36" valve discount  
Series 55 OS&Y valves reflect pricing for bevel gearing standard. Manually operated OS&Y's coming soon.

**Series 55/FFO/GB  
LARGE DIAMETER C515  
FLxFL OS&Y  
WITH GEARBOX**

Full wall ductile iron  
Flanged ends to  
ANSI B 16.1,  
Class 150 NRS  
250 PSI  
Size 18", 20", 24"



55-450-FFO-GB	18"	599	1321	34,690
55-500-FFO-GB	20"	639	1408	42,050
55-600-FFO-GB	24"	856	1886	56,560

Use 14"-36" valve discount  
Series 55 OS&Y valves reflect pricing for bevel gearing standard. Manually operated OS&Y's coming soon.