

SERIES 24 AWWA C503, WET BARREL

HYDRANT

American AVK Wet Barrel Hydrant Class Code/ Ref. # / Breakdown

24A - **BBB**
 └── Series no. └── Outlets

I - Ductile Iron
S - Stainless Steel

**PHH - 1 Pumper,
 2 Hose Outlets**
**PHN - 1 Pumper,
 1 Hose Outlet**
**PPH - 2 Pumps,
 1 Hose Outlet**

Series 24 AWWA C503 Availability Listing




Material	PHN 1 Pumper – 1 Hose Outlet	PHH 1 Pumper – 2 Hose Outlets	PPH 2 Pumps – 1 Hose Outlet
24I – Ductile Iron – 250/350 PSI*	X	X	X
24S – Stainless Steel – 200 PSI	X	X	X







* - As of June, 2020, all ductile iron wet barrel hydrants have been changed to the threaded high pressure configuration.

AWWA C503 WET BARREL HYDRANT ACRONYMS :

AWWA - American Water Works Association
DI - Ductile Iron
EPDM - Ethylene Propylene Diene Monomer
FL - Flange
FM - Factory Mutual

PE - Polyethylene
PUR - Polyurethane
SS - Stainless Steel
THD - Threaded
UL - Underwriters Laboratories

Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
Series 24T/PHH (2492) Wet barrel hydrant Ductile Iron, High Pressure To AWWA C503 UL Listed FM Approved 2 Hose Nozzles 1 Pumper Nozzle UL/FM - 250 PSI AWWA - 350 PSI		24T/PHH	2 x 2.5" and 1 x 4"	62	136	4,085
		24T/PHH	2 x 2.5" and 1 x 4.5"	62	136	4,085
Series 24T/PHN (2472) Wet barrel hydrant Ductile Iron, High Pressure To AWWA C503 UL Listed FM Approved 1 Hose Nozzle 1 Pumper Nozzle UL/FM - 250 PSI AWWA - 350 PSI		24T/PHN	1 x 2.5" and 1 x 4"	57	126	2,941
		24T/PHN	1 x 2.5" and 1 x 4.5"	57	126	2,941
Series 24T/PPH (2422) Wet barrel hydrant Ductile iron To AWWA C503 UL Listed 1 Hose Nozzle 2 Pumper Nozzles UL - 250 PSI AWWA - 350 PSI		24IT/PPH	1 x 2.5" and 2 x 4"	58	127	4,575
		24IT/PPH	1 x 2.5" and 2 x 4.5"	58	127	4,575
6 hole bolting options only						

Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
Series 24S/PHH (245X) Wet barrel hydrant Stainless Steel To AWWA C503 UL Listed FM Approved 2 Hose Nozzles 1 Pumper Nozzle 200 PSI		24S/PHH	2 x 2.5" and 1 x 4"	57	126	8,991
		24S/PHH	2 x 2.5" and 1 x 4.5"	57	126	8,991
Series 24S/PHN (244X) Wet barrel hydrant Stainless Steel To AWWA C503 UL Listed FM Approved 1 Hose Nozzle 1 Pumper Nozzle 200 PSI		24S/PHN	1 x 2.5" and 1 x 4"	46	101	6,597
		24S/PHN	1 x 2.5" and 1 x 4.5"	46	101	6,597
Series 24S/PPH (243X) Wet barrel hydrant Stainless Steel To AWWA C503 UL Listed 1 Hose Nozzle 2 Pumper Nozzle 200 PSI		24S/PPH	1 x 2.5" and 2 x 4"	46	101	9,491
		24S/PPH	1 x 2.5" and 2 x 4.5"	46	101	9,491
Series 24/80 Breakable flange unit for AVK Wet barrel hydrants		24-150-80	Kit with bolts included	19	42	463
			For 304 Bolts			add 81
			For 316 Bolts			add 161
Use Hydrant Parts discount						
Series 24/82 Break ring Repair kit for AVK Wet barrel hydrant breakable flange unit		24-150-82X	Kit with bolts included	7	15	269
			For 304 Bolts			add 81
			For 316 Bolts			add 161
Option: X =1.Bolts, nuts and washers plated steel 2.Bolts, nuts and washers stainless steel Use Hydrant Parts discount						
Series 24/88X FlowGuard II™ check valve unit for AVK Wet barrel hydrants		24-150-88X	FlowGuard II™ Kit, bolts included	19	42	2,401
			For 304 Bolts			add 81
			For 316 Bolts			add 161
Use Hydrant Parts discount						