



Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
<p><b>Series 65/HFN</b> <b>REDUCED WALL DUCTILE</b> <b>HY X FL To AWWA C515</b></p>  <p>HYMAX GRIP® X Flanged end to ANSI B 16.1 Class 125 NRS Ductile iron 250 PSI Size 4"-12"</p>	65-100-HFN	4"	34	73	1,347	
	65-150-HFN	6"	54	119	1,811	
	65-200-HFN	8"	78	170	2,717	
	65-250-HFN	10"	115	253	4,277	
	65-300-HFN	12"	151	331	5,357	
	<p><b>Series 65/HHN</b> <b>REDUCED WALL DUCTILE</b> <b>HY X HY To AWWA C515</b></p>  <p>HYMAX GRIP® ends Class 150 NRS Ductile iron 250 PSI Size 1.5"-12"</p>	65-050-HHN	1.5"-2"	38	83	1,068
65-065-HHN		2.5"	38	83	1,293	
65-080-HHN		3"	38	83	1,436	
65-100-HHN		4"	38	83	1,599	
65-150-HHN		6"	60	131	2,123	
65-200-HHN		8"	88	193	3,329	
65-250-HHN		10"	127	279	4,843	
65-300-HHN		12"	159	349	6,017	