

# SERIES 764 – ECCENTRIC

# PLUG VALVE

## UL/FM PRODUCTS FOR FIRE PROTECTION ACRONYMS :

**ANSI** - American National Standards Institute  
**ASME** - American Society of Mechanical Engineers  
**AWWA** - American Water Works Association  
**DIPS** - Ductile Iron Pipe Size  
**EPDM** - Ethylene Propylene Diene Monomer  
**FL** - Flange  
**FM** - Factory Mutual  
**GR** - Grooved  
**HDPE** - High Density Polyethylene  
**IPS** - Iron Pipe Size  
**MJ** - Mechanical Joint

**NBR** - Nitrile Butyl Rubber  
**NRS** - Non Rising Stem  
**NPT** - National Pipe Thread  
**OS&Y** - Outside Screw/Stem & Yoke  
**PE** - Polyethylene  
**PIV** - Post Indicator Valve  
**PO** - Push - On  
**PUR** - Polyurethane  
**SS** - Stainless Steel  
**UL** - Underwriters Laboratories

AWWA C517, ECCENTRIC PLUG VALVES

Type	AVK Ref. #	Size	Weight		Price US \$
			kg	lb	
<b>Series 764/FFGB ECCENTRIC PLUG VALVE WITH GEARBOX FL X FL To AWWA C517</b>  Flanged end to ANSI B 16.1 Class 125 Ductile iron 250 PSI Size 2½"-12"					
	764-065-FFGB	2.5"	26	56	1,360
	764-080-FFGB	3"	32	69	1,770
	764-100-FFGB	4"	39	86	1,974
	764-150-FFGB	6"	62	135	2,716
	764-200-FFGB	8"	102	223	3,772
	764-250-FFGB	10"	173	380	5,268
	764-300-FFGB	12"	224	494	6,864

