

## AVK Series 766, Double Eccentric Butterfly Valve Class Code/ Ref. # / Breakdown

766 - Series No.	XXXX - Size	XX - Flange Configuration	XX - Actuation	X - Opening Direction	X - Testing Pressure	X - Test Direction
	0600 - 24" 0750 - 30" 0900 - 36" 1050 - 42" 1200 - 48"	FF - FLxFL MM - MJxMJ	AG - Above Ground BG - Below Ground BS - Bare Shaft	L - Open Left R - Open Right B - Both *	L - 150 PSI H - 250 PSI	1 - Single 2 - Bi-directional

\* - Only on bare stem valves


### SERIES 766, DOUBLE ECCENTRIC BUTTERFLY VALVE ACRONYMS :

ANSI - American National Standards Institute  
 ASME - American Society of Mechanical Engineers  
 AWWA - American Water Works Association  
 DI - Ductile Iron  
 EPDM - Ethylene Propylene Diene Monomer  
 FL - Flange  
 MJ - Mechanical Joint  
 WAF - Wafer  
 FF - Flange x Flange  
 MF - Mechanical Joint x Flange  
 WW - Wafer

**Type**

**Series766/FF/RGB-1  
DOUBLE ECCENTRIC  
BUTTERFLY VALVE  
To AWWA C504**

Flanged end to ANSI B 16.1  
Class 125  
Ductile iron  
250 PSI  
Size 24"-48"



**AVK Ref. #**

**Size**

**Weight**

kg

lb

**Price**


US \$

766-0600-FF-RGB-H	24"	425	936	11,808
766-0750-FF-RGB-H	30"	764	1684	20,280
766-0900-FF-RGB-H	36"	1130	2490	24,600
766-1050-FF-RGB-H	42"	1685	3715	38,100
766-1200-FF-RGB-H	48"	2282	5029	49,140

Specify above ground, or below ground intallation when ordering


**Series766/FF/RGB-2  
DOUBLE ECCENTRIC  
BUTTERFLY VALVE  
To AWWA C504**


Flanged end to ANSI B 16.1  
Class 125  
Ductile iron  
250 PSI  
Size 24"-48"  
Bi-Directional Testing



766-0600-FF-RGB-H2	24"	425	936	12,989
766-0750-FF-RGB-H2	30"	764	1684	22,308
766-0900-FF-RGB-H2	36"	1130	2490	27,060
766-1050-FF-RGB-H2	42"	1685	3715	41,910
766-1200-FF-RGB-H2	48"	2282	5029	54,054

Specify above ground, or below ground intallation when ordering

Type	AVK Ref. #	Size	Weight		Price US \$
			kg	lb	
<b>Series766/MM/RGB-1 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504</b>  Mechanical Joint ends  Ductile iron 250 PSI Size 24"-48"					
	766-0600-MM-RGB-H	24"	429	944	11,808
	766-0750-MM-RGB-H	30"	756	1667	20,280
	766-0900-MM-RGB-H	36"	1160	2557	24,600
	766-1050-MM-RGB-H	42"	1720	3790	38,100
	766-1200-MM-RGB-H	48"	2309	5111	49,140
Specify above ground, or below ground intallation when ordering					

<b>Series766/MM/RGB-2 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504</b>  Mechanical Joint ends  Ductile iron 250 PSI Size 24"-48" Bi-Directional Testing					
	766-0600-MM-RGB-H2	24"	429	944	12,989
	766-0750-MM-RGB-H2	30"	756	1667	22,308
	766-0900-MM-RGB-H2	36"	1160	2557	27,060
	766-1050-MM-RGB-H2	42"	1720	3790	41,910
	766-1200-MM-RGB-H2	48"	2309	5111	54,054
Specify above ground, or below ground intallation when ordering					

AWWA C504, DOUBLE ECCENTRIC, RESILIENT SEATED BUTTERFLY VALVES