

EXPECT SOLUTIONS,  
NOT JUST  
PRODUCTS

Expect... **AVK**

# TABLE OF CONTENTS

IN DIGITAL VERSION, PAGE NUMBERS ARE LINKED TO PAGES -  
CLICK ON ANY "Expect AVK" LOGO TO RETURN TO TABLE OF CONTENTS

---

## 2 TABLE OF CONTENTS

---

### 3 RESILIENT WEDGE GATE VALVES FOR FIRE PROTECTION

- 145/FFN - FLxFL - NRS
- 145/FFO - FLxFL - OS&Y
- 145/GFN - GRxFL - NRS
- 145/GFO - GRxFL - OS&Y
- 145/GGN - GRxGR - NRS

### 4 • 145/GGO - GRxGR - OS&Y

---

### 4 SERIES 5190 SPRING LOADED GROOVED END CHECK VALVES

- 5190/SCV - GRVxGRV

---

### 5 RESILIENT WEDGE GATE VALVES FOR TELESCOPING INDICATOR POSTS

- 45/FFN/FP - FLxFL - NRS
- 45/MFN/FP - MJxFL - NRS
- 45/MMN/FP - MJxMJ - NRS

---

### 5 RESILIENT WEDGE GATE VALVES GROOVED - NRS

- 45/GFN/FP - GVxFL - NRS
- 45/GGN/FP - GVxGV - NRS

---

### 6 RESILIENT WEDGE GATE VALVES GROOVED - OS&Y

- 45/FFO/FP - FLxFL - OS&Y
- 45/GFO/FP - GVxFL - OS&Y
- 45/GGO/FP - GVxGV - OS&Y

---

### 7 SERIES 34 INDICATOR POSTS






- 340X/TIP - TELESCOPING POST
- 348X/WIP - WALL POST

---

### 8 SERIES 45 & 145 WARRANTY

### 9 SERIES 5190 WARRANTY


### 10 SERIES 34 WARRANTY

Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
<b>Series 145/FFN</b> <b>FL X FL, Fire Protection Only</b> <b>Ductile iron body</b> UL listed and FM approved Flanged ends NRS NRS 250 PSI Size 2½"-8"		145-065-FFN	2½"	13	28	440
		145-080-FFN	3"	17	38	480
		145-100-FFN	4"	22	48	880
		145-150-FFN	6"	43	95	1,260
		145-200-FFN	8"	77	169	2,120
		<b>Series 145/FFO</b> <b>FL x FL OS&amp;Y</b> <b>Ductile iron body</b> UL listed and FM approved Flanged ends OS&Y 250 PSI Size 2½"-8"		145-065-FFO	2½"	15
145-080-FFO	3"			19	41	760
145-100-FFO	4"			27	58	900
145-150-FFO	6"			51	112	1,320
145-200-FFO	8"			88	194	2,250
<b>Series 145/GFN</b> <b>GV X FL, Fire Protection Only</b> <b>Ductile iron body</b> UL listed and FM approved to AWWA C606 Grooved ends (IPS) Flanged ends NRS NRS 250 PSI Size 2½"-8"				145-065-GFN	2½"	9
		145-080-GFN	3"	14	29	460
		145-100-GFN	4"	15	32	860
		145-150-GFN	6"	32	70	1,240
		145-200-GFN	8"	70	154	2,100
		<b>Series 145/GFO</b> <b>GV x FL OS&amp;Y</b> <b>Ductile iron body</b> UL listed and FM approved to AWWA C606 Grooved ends (IPS) Flanged ends OS&Y 250 PSI Size 2½"-8"		145-065-GFO	2½"	11
145-080-GFO	3"			14	30	740
145-100-GFO	4"			19	41	880
145-150-GFO	6"			43	94	1,300
145-200-GFO	8"			84	184	2,540
<b>Series 145/GGN</b> <b>GV X GV, Fire Protection Only</b> <b>Ductile iron body</b> UL listed and FM approved to AWWA C606 Grooved ends (IPS) NRS 250 PSI Size 2½"-8"				145-065-GGN	2½"	10
		145-080-GGN	3"	14	29	450
		145-100-GGN	4"	15	32	850
		145-150-GGN	6"	32	70	1,230
		145-200-GGN	8"	70	154	2,090

**Type**

**Series 145/GFO  
GV X GV, Fire Protection  
Only  
Ductile iron body**

UL listed and  
FM approved  
to AWWA C606  
Grooved ends (IPS)  
OS&Y  
250 PSI  
Size 2½"-8"



**AVK Ref. #**

**Size**

**Weight  
kg lb**

**Price  
US \$**

145-065-GGO	2½"	11	23	690
145-080-GGO	3"	14	30	730
145-100-GGO	4"	19	41	870
145-150-GGO	6"	43	94	1,290
145-200-GGO	8"	84	184	2,530






**Series 5190/SCV  
GR X GR Swing Check Valve  
Spring Loaded  
Ductile iron body**




UL listed and  
FM approved  
Grooved ends (IPS)  
to AWWA C606  
250 PSI  
Size 2½"-8"



5190-065-SCV	2½"	4	9	360
5190-080-SCV	3"	7	14	400
5190-100-SCV	4"	9	20	420
5190-150-SCV	6"	19	42	720
5190-200-SCV	8"	34	78	900

Add \$40 for shotgun configuration


Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
<b>Series 45/FFP/FP</b> <b>FL X FL, PIV,</b> <b>Full wall ductile iron</b> <b>125 lb. Flange</b> to AWWA C509/C515 UL listed and FM approved Flanged ends to ASME B 16.42 Class 150 NRS 250 PSI Size 4"-12"		45-100-FFP-FP	4"	38	84	1,421
	45-150-FFP-FP	6"	63	139	1,811	
	45-200-FFP-FP	8"	82	181	2,685	
	45-250-FFP-FP	10"	121	267	4,111	
	45-300-FFP-FP	12"	174	391	4,911	
	<b>Series 45/MFP/FP</b> <b>MJ X FL, PIV,</b> <b>Full wall ductile iron</b> to AWWA C509/C515 UL listed and FM approved Mechanical joint end X Flanged end ASME B 16.42 Class 150 NRS 250 PSI Size 4"-12"		45-100-MFP-FP	4"	28	62
45-150-MFP-FP		6"	47	103	1,755	
45-200-MFP-FP		8"	71	155	2,639	
45-250-MFP-FP		10"	109	240	3,969	
45-300-MFP-FP		12"	153	337	4,953	
less MJ accessories						
<b>Series 45/MMP/FP</b> <b>FMJ X MJ, PIV,</b> <b>Full wall ductile iron</b> to AWWA C509/C515 UL listed and FM approved Mechanical joint ends NRS 250 PSI Size 4"-12"		45-100-MMP-FP	4"	28	62	1,431
	45-150-MMP-FP	6"	47	103	1,755	
	45-200-MMP-FP	8"	71	155	2,639	
	45-250-MMP-FP	10"	109	240	3,969	
	45-300-MMP-FP	12"	153	337	4,953	
	less MJ accessories					
<b>Series 45/GFN/FP</b> <b>IPS GR X FL</b> <b>Ductile iron body</b> UL listed and FM approved to AWWA C606 Grooved ends (IPS) Flanged ends to ASME B 16.42 Class 150 NRS 250 PSI Size 2½"-10"		45-065-GFN-FP	2½"	15	33	1,054
	45-080-GFN-FP	3"	16	35	1,247	
	45-100-GFN-FP	4"	21	55	1,393	
	45-150-GFN-FP	6"	40	87	1,863	
	45-200-GFN-FP	8"	61	133	2,908	
	45-250-GFN-FP	10"	94	208	4,640	
	<b>Series 45/GGN</b> <b>IPS GR X GR</b> <b>Ductile iron body</b> UL listed and FM approved to AWWA C606 Grooved ends (IPS) NRS 250 PSI Size 2½"-10"		45-065-GGN-FP	2½"	14	30
45-080-GGN-FP		3"	16	35	1,247	
45-100-GGN-FP		4"	21	46	1,393	
45-150-GGN-FP		6"	40	87	1,863	
45-200-GGN-FP		8"	61	133	2,908	
45-250-GGN-FP		10"	83	182	4,640	

Type	AVK Ref. #	Size	Weight		Price US \$	
			kg	lb		
<b>Series 45/FFO</b> <b>FL X FL OS&amp;Y</b> <b>Full wall ductile iron</b> <b>125 lb. Flange</b> to AWWA C509/C515 UL listed and FM approved Flanged ends to ASME B 16.42 Class 150 OS&Y 250 PSI Size 2.5"-12"		45-065-FFO	2.5"	19	42	1,145
	45-080-FFO	3"	25	56	1,335	
	45-100-FFO	4"	35	78	1,527	
	45-150-FFO	6"	54	118	1,983	
	45-200-FFO	8"	85	187	3,029	
	45-250-FFO	10"	152	335	4,451	
	45-300-FFO	12"	209	461	5,795	
<b>Series 45/GFO/FP</b> <b>IPS GR X FL OS&amp;Y</b> <b>Ductile iron body</b> to AWWA C606 UL listed and FM approved Grooved ends (IPS) Flanged ends to ASME B 16.42 Class 150 NRS 250 PSI Size 2½"-10"		45-065-GFO-FP	2½"	21	45	1,151
	45-080-GFO-FP	3"	18	48	1,372	
	45-100-GFO-FP	4"	26	64	1,532	
	45-150-GFO-FP	6"	47	111	2,040	
	45-200-GFO-FP	8"	72	165	3,343	
	45-250-GGO	10"	125	275	5,135	
<b>Series 45/GGO/FP</b> <b>IPS GR X GR OS&amp;Y</b> <b>Ductile iron body</b> Grooved ends (IPS) to AWWA C606 UL listed and FM approved OS&Y 250 PSI Size 2½"-10"		45-065-GGO-FP	2½"	16	35	1,151
	45-080-GGO-FP	3"	18	40	1,372	
	45-100-GGO-FP	4"	26	56	1,532	
	45-150-GGO-FP	6"	47	103	2,040	
	45-200-GGO-FP	8"	72	157	3,343	
	45-250-GGO-FP	10"	119	262	5,135	

**Type**

**Series 34/OX  
Telescopic Indicator Post  
Above ground  
Up-right model**

UL listed and  
FM approved




AVK Ref. #	Weight - Poly		Weight - Steel		Price - Poly	Price - Steel
	kg	lb	kg	lb	US \$	US \$

34-0A	xxx	158	xxx	180	1,799	2,210
34-0B	xxx	180	xxx	188	2,077	2,900
34-0C	xxx	219	xxx	219	2,243	3,230
34-0D	xxx	xxx	xxx	258	2,443	3,530
34-0E	xxx	xxx	xxx	xxx	2,643	3,830
34-0F	xxx	xxx	xxx	336	2,843	4,130

Refer to Datasheet for A,B,C,D,E,F minimum-maximum lengths

**Series 34/8X  
Indicator post  
Wall model**

UL listed and  
FM approved



	Stem Length			
	In.			
34-130-8X	30"	37.0	81	1,793
34-150-8X	50"	34.0	75	1,883

Contact Customer Service for custom stem length



---

## **AMERICAN AVK COMPANY TWO (2) YEAR WARRANTY RESILIENT WEDGE GATE VALVES FOR FIRE PROTECTION**

American AVK Company warrants its Series 45 and 145 Resilient Wedge Gate Valves to be free from defects in workmanship and materials for a period of two (2) years from the date of shipment from American AVK Company. American AVK Company shall have no obligation under this warranty unless it is notified of claims hereunder promptly and in writing upon discovery thereof and within the warranty period, and unless the product is delivered to the American AVK Company facility within thirty (30) days of such notice.

American AVK shall have the right to inspect said product before it is removed from installation. If the product is removed from installation prior to approval from American AVK this warranty shall be void.

As to motors, gearing or accessory equipment purchased by American AVK Company from others manufacturers, and used or incorporated into American AVK Company's products, those manufacturers' warranties shall apply.

American AVK Company will honor all reasonable costs to repair or replace any American AVK Company Resilient Wedge Gate Valve found to be defective.

American AVK Company's sole responsibility shall be, in its sole discretion, to replace the product with the same or a similar product, repair the product, or refund the price paid for the product provided the product has been properly applied and used under normal service and under conditions for which it is designed. American AVK Company shall not be liable for indirect, special, incidental, or consequential damage or penalties and does not assume any liability of purchase to others or to anyone for injury to persons or property.

**THIS IS THE EXCLUSIVE WARRANTY GIVEN IN CONNECTION WITH THE SALE OF THIS PRODUCT. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING EXPRESSED OR IMPLIED WARRANTY OF MERCHANTABILITY, OR ANY EXPRESSED OR IMPLIED WARRANTY OF SUITABILITY FOR ANY PARTICULAR PURPOSE, GIVEN BY AMERICAN AVK COMPANY IN CONNECTION WITH THIS PRODUCT.**

---

### **American AVK Company**

2155 Meridian Blvd  
Minden, NV 89423

Tel: (775) 552-1400  
Fax: (775) 783-1031

sales@avkus.com  
[www.americanavk.com](http://www.americanavk.com)







---

## **AMERICAN AVK COMPANY ONE (1) YEAR WARRANTY CHECK VALVES FOR FIRE PROTECTION**

American AVK Company warrants its Series 5190, Check Valves to be free from defects in workmanship and materials for a period of one (1) years from the date of shipment from American AVK Company. American AVK Company shall have no obligation under this warranty unless it is notified of claims hereunder promptly and in writing upon discovery thereof and within the warranty period, and unless the product is delivered to the American AVK Company facility within thirty (30) days of such notice.

American AVK shall have the right to inspect said product before it is removed from installation. If the product is removed from installation prior to approval from American AVK this warranty shall be void.

As to motors, gearing or accessory equipment purchased by American AVK Company from others manufacturers, and used or incorporated into American AVK Company's products, those manufacturers' warranties shall apply.

American AVK Company will honor all reasonable costs to repair or replace any American AVK Company Check Valve found to be defective.

American AVK Company's sole responsibility shall be, in its sole discretion, to replace the product with the same or a similar product, repair the product, or refund the price paid for the product provided the product has been properly applied and used under normal service and under conditions for which it is designed. American AVK Company shall not be liable for indirect, special, incidental, or consequential damage or penalties and does not assume any liability of purchase to others or to anyone for injury to persons or property.

**THIS IS THE EXCLUSIVE WARRANTY GIVEN IN CONNECTION WITH THE SALE OF THIS PRODUCT. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING EXPRESSED OR IMPLIED WARRANTY OF MERCHANTABILITY, OR ANY EXPRESSED OR IMPLIED WARRANTY OF SUITABILITY FOR ANY PARTICULAR PURPOSE, GIVEN BY AMERICAN AVK COMPANY IN CONNECTION WITH THIS PRODUCT.**

---

### **American AVK Company**

2155 Meridian Blvd  
Minden, NV 89423

Tel: (775) 552-1400  
Fax: (775) 783-1031

sales@avkus.com  
[www.americanavk.com](http://www.americanavk.com)





---

## **AMERICAN AVK COMPANY ONE (1) WARRANTY YEAR SERIES 3400/3480 POST INDICATOR**

American AVK Company warrants its Series 3400 and 3480 Post Indicator to be free from defects in workmanship and materials for a period of one (1) year from the date of shipment from American AVK Company. American AVK Company shall have no obligation under this warranty unless it is notified of claims hereunder promptly and in writing upon discovery thereof and within the warranty period, and unless the product is delivered to American AVK Company within thirty (30) days of such notice.

American AVK shall have the right to inspect said product before it is removed from installation. If the product is removed from installation prior to approval from American AVK this warranty shall be void.

As to motors, gearing or accessory equipment purchased by American AVK Company from other manufacturers, and used or incorporated into American AVK Company's products, those manufacturers' warranties shall apply.

American AVK Company's sole responsibility shall be, in its sole discretion, to replace the product with the same or a similar product, repair the product, or refund the price paid for the product provided the product has been properly applied and used under normal service and under conditions for which it is designed. American AVK Company shall not be liable for indirect, special, incidental, or consequential damage or penalties and does not assume any liability of purchase to others or to anyone for injury to persons or property.

**THIS IS THE EXCLUSIVE WARRANTY GIVEN IN CONNECTION WITH THE SALE OF THIS PRODUCT. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING EXPRESSED OR IMPLIED WARRANTY OF MERCHANTABILITY, OR ANY EXPRESSED OR IMPLIED WARRANTY OF SUITABILITY FOR ANY PARTICULAR PURPOSE, GIVEN BY AMERICAN AVK COMPANY IN CONNECTION WITH THIS PRODUCT.**

---

### **American AVK Company**

2155 Meridian Blvd  
Minden, NV 89423

Tel: (775) 552-1400  
Fax: (775) 783-1031

sales@avkus.com  
[www.americanavk.com](http://www.americanavk.com)

