

AMERICAN AVK HIGH PRESSURE, 250 PSI, MODERN, DUAL PUMPER, DRY BARREL HYDRANT, 5,25" MAIN VALVE

27M/PPN MODERN DUAL PUMPER

Meets or exceeds AWWA C502 (latest) - Working Pressure - 250 PSI

Inlet Bases: Flanged in accordance with ANSI B16.1 Class 125,

Mechanical and Push-On Joint in accordance with ANSI/AWWA C111/A21.11

Use:

For water and neutral liquids to maximum 160°F.

Tests:

Hydraulic test to AWWA C502:

Seat Test: 500 PSI

Approvals:
UL/ULC Listed
Certified to:
NSF/ANSI 61
NSF/ANSI 372



Components:

Nozzle Section, Upper Barrel, Barrels, Standpipe Flanges,
Breakable Flange, Main Valve Flange, Base, Monitor Elbow

Caps, Weathershield

Nozzles, Valve Seat Ring, Drain Ring
Operating Nut, Thrust Nut

Brass Fittings, Brass Plugs

Main Valve

Stem Rod Couplings, Lock Rings, Nozzle Retaining
Screw, Lock Plate, Lock Plate Screw, Stop Pins,
Coupler Pins, Main Valve Retaining Pin, Spring Pins,

Coating

Stop Nut, Chain Set, Hardware

Barrel Gasket, Cap Gasket, O-rings

Lubrication Hole Seal

Anti-Friction Washer

Base Elbow / Inlet Configuration	☐ 6" MJ	☐ 6" Flanged	☐ 6" Push-on	☐ 6" Hymax Grip® *
	☐ 4" MJ	☐ 4" Flanged	☐ 4" PE*	
	☐ 8" MJ*	☐ 6" Straight Flanged	☐ 6" PE*	

*Not UL/ULC Listed or FM Approved

Standard:

Ductile Iron ASTM A536

Cast Iron ASTM A126 Class "B"

Bronze

Brass

Ductile iron core, fully encapsulated with EPDM rubber.

Stainless Steel

Above ground-Fusion bonded epoxy inside and out. Below
ground - Bitumen/Fusion bonded epoxy. Epoxy meets or
exceeds AWWA C550 (latest)

Zinc Plated Steel


NBR - (Barrel Gasket with 304 stainless insert)

Oil Resistant Rubber

Polyamide

Optional Materials:

Hardware - Above Ground	☐ Zinc Plated (Standard)	☐ 304 Stainless	☐ 316 Stainless
Hardware - Below Ground	☐ 304 Stainless (Standard)	☐ Zinc Plated	☐ 316 Stainless
Upper Stem Rod	☐ 304 Stainless (Standard)	☐ Mild Steel	☐ Bronze
Lower Stem Rod	☐ Mild Steel (Standard)	☐ 304 Stainless	☐ Bronze
Caps, Weathershield	☐ Cast Iron (Standard)	☐ Ductile Iron	
Opening Direction	☐ Open Left	☐ Open Right	



Series 27M/PPN
2 Pumper



AMERICAN AVK HIGH PRESSURE, 250 PSI, MODERN, DUAL PUMPER, DRY BARREL HYDRANT, 5,25" MAIN VALVE

27M/PPN MODERN DUAL PUMPER



Meets or exceeds AWWA C502 (latest) - Working Pressure - 250 PSI

Inlet Bases: Flanged in accordance with ANSI B16.1 Class 125,

Mechanical and Push-On Joint in accordance with ANSI/AWWA C111/A21.11

Component List:

- | | | | |
|----------------------------|----------------------------|----------------------------------|----------------------------------|
| 1. Weathershield Bolt | 23. Nozzle Retaining Screw | 37. Breakable Stem Rod | 60. Main Valve Retaining Pin |
| 2. Weathershield | 24. Chain Set | Coupling | -Detail A |
| 3. Lock Plate Screw | 25. Pumper Nozzle O-ring | 38. Spring Pin | 61. Main Valve Disc -Detail A |
| 4. Lock Plate | 26. Pumper Nozzle | 41. Lower Stem Rod | 67. Base |
| 5. Inner Thrust Nut O-ring | 27. Pumper Nozzle Gasket | 46. Standpipe Flange -Detail A | 69. Thrust Bearing |
| 6. Thrust Nut | 28. Pumper Nozzle Cap | 49. Lower Barrel | 71. Modern Nozzle Section |
| 7. Outer Thrust Nut O-ring | 29. Nozzle Section | 50. Lower Barrel O-ring Detail A | Bolt |
| 8. Anti-Friction Washer | 30. Nozzle Section Bolt | 51. Valve Seat Ring -Detail A | 75. Zerk Fitting (not shown) |
| 9. Lubrication Hole Seal | 31. Nozzle Section Washer | 53. Valve Seat O-ring -Detail A | 506. Hydrant Base Bolt -Detail A |
| 10. Operating Nut | 32. Lock Ring | 54. Drain Ring -Detail A | |
| 11. Stop Nut | 33. Breakable Flange | 55. Brass Plug -Not shown | |
| 15. Stem Seal O-rings | 34. Nozzle Section Nut | 56. Brass Fitting -Not shown | |
| 16. Upper Stem Rod | 35. Upper Barrel | | |
| 17. Barrel Gasket | 36. Coupler Pin | | |



Ref No.	Base Size	Outlets	A	B*	C Flanged	C MJ	C Push-on	C PE	C HYMAX GRIP®
27M-PPN-4	- 4"	2x4"/4½"	67" - 265"	18" - 216"	8.00"	8.00"	N/A	23.70"	N/A
27M-PPN-6	- 6"	2x4"/4½"	67" - 265"	18" - 216"	8.00"	8.00"	9.00"	22.80"	11.60"
27M-PPN-8	- 8"	2x4"/4½"	67" - 265"	18" - 216"	N/A	9.38"	N/A	N/A	N/A

* Buries greater than 216" available upon request.

