


AMERICAN AVK RESILIENT SEATED DUCTILE IRON GATE VALVE
250/350 PSI, Tested to AWWA C509 / C515 (NRS)
Push-on Joint End x Push-on Joint End - Valve sizes 4" - 12" and 16"

45/PPN-WD
POxPO

Component List:

217. Bonnet
218. Bonnet Gasket
219. Body
225. Wrench Nut
226. Wiper Ring
227. Gland Flange Bolt
228. Gland Flange
229. Gland O-Ring
230. Upper Stem Seal O-Rings
231. Stem Seal Bushing
232. Lower Stem Seal O-Ring
233. NRS Stem
234. Thrust Collar
237. Wedge



Ref No.	Size	Working Pressure	D	E	H	L	M	Turns to Open	Weight (lbs.)
45-100-PPN-WD	4"	350	6.66"	4.93"	13.50"	11.99"	4.12"	14	57
45-150-PPN-WD	6"	350	8.84"	7.03"	17.50"	15.63"	5.22"	20	97
45-200-PPN-WD	8"	350	11.23"	9.18"	21.50"	17.17"	5.63"	26	157
45-250-PPN-WD	10"	350	13.50"	11.22"	24.75"	17.64"	5.63"	32	227
45-300-PPN-WD	12"	350	15.74"	13.32"	27.75"	19.21"	5.63"	38	391
45-400-PPN-WD	16"	250	20.62"	17.50"	34.75"	22.72"	6.00"	54	982

